

In re Patent Application of:  
**KURDZIEL ET AL.**  
Serial No. **10/780,848**  
Confirmation No. **2513**  
Filed: **FEBRUARY 18, 2004**

---

**In the Claims:**

1. (Currently Amended) A cryptographic device comprising:  
an input stage receiving an input data block and a key data block comprising a plurality of sub-key data blocks, and generating a plurality of first signals therefrom that are in parallel;  
an intermediate stage connected to said input stage and comprising  
a plurality of substitution units operating in parallel, each substituting data within a respective first signal, and  
a diffuser connected to said plurality of substitution units for mixing data to generate a diffused signal; and  
an output stage connected to said intermediate stage for repetitively looping back the diffused signal to said input stage for combination with a next sub-key data block.
2. (Original) A cryptographic device according to Claim 1 wherein the looping back is repeated a predetermined number of times; and wherein said output stage provides an output signal for the cryptographic device after the repetitively looping back is complete.
3. (Original) A cryptographic device according to Claim 2 wherein the output signal is further combined with a final sub-key data block.

In re Patent Application of:

**KURDZIEL ET AL.**

Serial No. **10/780,848**

Confirmation No. **2513**

Filed: **FEBRUARY 18, 2004**

---

4. (Original) A cryptographic device according to Claim 1 wherein each substitution unit performs a non-linear substitution based upon at least one look-up table.

5. (Original) A cryptographic device according to Claim 1 wherein said diffuser comprises a shift register and a look-up table associated therewith.

6. (Original) A cryptographic device according to Claim 1 wherein said diffuser comprises a plurality of shift registers and a plurality of look-up tables associated therewith.

7. (Original) A cryptographic device according to Claim 1 wherein said output stage performs a row-shift operation on the diffused output signal before being looped back to said input stage.

8. (Original) A cryptographic device according to Claim 1 wherein said output stage performs a column-mix operation on the diffused output signal being looped back to said input stage.

9. (Original) A cryptographic device according to Claim 1 wherein said output stage comprises a counter for counting a number of times the diffused output signal is looped back to said input stage.

In re Patent Application of:

**KURDZIEL ET AL.**

Serial No. **10/780,848**

Confirmation No. **2513**

Filed: **FEBRUARY 18, 2004**

---

10. (Currently Amended) A communication system comprising:

a key scheduler providing a key data block comprising a plurality of sub-key data blocks; and

a cryptographic device connected to said key scheduler and comprising

an input stage receiving an input data block and the key data block, and generating a plurality of first signals therefrom that are in parallel;

an intermediate stage connected to said input stage and comprising

a plurality of substitution units operating in parallel, each substituting data within a respective first signal, and

a diffuser connected to said plurality of substitution units for mixing data to generate a diffused signal, and

an output stage connected to said intermediate stage for repetitively looping back the diffused signal to said input stage for combination with a next sub-key data block; said output stage providing an output signal for the cryptographic device after the repetitively looping back is complete.

11. (Original) A communication system according to Claim 10 wherein the output signal is further combined with a final sub-key data block.

In re Patent Application of:  
**KURDZIEL ET AL.**  
Serial No. **10/780,848**  
Confirmation No. **2513**  
Filed: **FEBRUARY 18, 2004**

---

12. (Original) A communication system according to Claim 10 wherein each substitution unit performs a non-linear substitution based upon at least one look-up table.

13. (Original) A communication system according to Claim 10 wherein said diffuser comprises a shift register and a look-up table associated therewith.

14. (Original) A communication system according to Claim 10 wherein said diffuser comprises a plurality of shift registers and a plurality of look-up tables associated therewith.

15. (Original) A communication system according to Claim 10 wherein said output stage performs a row-shift operation on the diffused output signal before being looped back to said input stage.

16. (Original) A communication system according to Claim 10 wherein said output stage performs a column-mix operation on the diffused output signal being looped back to said input stage.

17. (Original) A communication system according to Claim 10 wherein said output stage comprises a counter for counting a number of times the diffused output signal is looped back to said input stage.

18. (Currently Amended) A method for converting an

In re Patent Application of:  
**KURDZIEL ET AL.**  
Serial No. **10/780,848**  
Confirmation No. **2513**  
Filed: **FEBRUARY 18, 2004**

---

input data block into an output signal in a cryptographic device,  
the method comprising:

generating a plurality of first signals that are in parallel based upon the input data block and a key data block comprising a plurality of sub-key data blocks;

substituting data within each first signal using a respective substitution unit, with the substitution units operating in parallel to one another;

mixing data to generate a diffused signal using a diffuser connected to the respective substitution units; and

repetitively looping back the diffused signal for combination with a next sub-key data block before repeating the substituting and mixing.

19. (Original) A method according to Claim 18 wherein the looping back is repeated a predetermined number of times; and further comprising providing an output signal for the cryptographic device after the repetitively looping back is complete.

20. (Original) A method according to Claim 19 further comprising combining the output signal with a final sub-key data block.

21. (Original) A method according to Claim 18 wherein each substitution unit performs a non-linear substitution based upon at least one look-up table.

In re Patent Application of:  
**KURDZIEL ET AL.**  
Serial No. **10/780,848**  
Confirmation No. **2513**  
Filed: **FEBRUARY 18, 2004**

---

22. (Original) A method according to Claim 18 wherein the diffuser comprises a shift register and a look-up table associated therewith.

23. (Original) A method according to Claim 18 wherein the diffuser comprises a plurality of shift registers and a plurality of look-up tables associated therewith.

24. (Original) A method according to Claim 18 further comprising performing a row-shift operation on the diffused output signal before being looped back.

25. (Original) A method according to Claim 18 further comprising performing a column-mix operation on the diffused output signal being looped back.

26. (Original) A method according to Claim 18 further comprising counting a number of times the diffused output signal is looped back.